

DESCRIPTION & USE

LEXCAN SINGLE PLY MEMBRANE CLEANER is a clear solvent, used for cleaning and preparing seam areas of EPDM, TPO, PVC and PVC KEE roofing membranes, for bonding, welding or application of seam tape.

FEATURES & BENEFITS

Compatibility - Cleans both new and in-service EPDM, TPO, PVC and PVC KEE membranes.

TECHNICAL DATA

Typical Physical Properties & Characteristics	
Colour:	Clear
Viscosity:	Water thin
Solids:	0%
Solvent Base and System:	Aromatic
Flash Point (ASTM D 56):	3.89°C (39°F)
Density:	0.87 kg/L (7.25 lb/gal)
VOC Content:	866 g/L

PACKAGING

3.79 L (1 Gallon) container

COVERAGE

4.9 - 6.1 m²/L (200-250 ft² / gallon) on single side coverage. The actual coverage depends significantly on the cleanliness of the surface.

STORAGE

Prevent this container from coming in contact with water. Store locked up and in a well-ventilated place.

SHELF LIFE

2 years when stored in original unopened containers at temperatures between 16°C (60°F) and 27°C (80°F).

APPLICATION

Note: Solvent resistant gloves should be used when applying this product.

1. Apply LEXCAN SINGLE PLY MEMBRANE CLEANER to the seam area with a clean rag or scrub pad.
2. Wipe the area until all surface contamination is removed.
3. Allow the cleaner to dry completely before bonding, welding or applying seam tape.



CAUTIONS & LIMITATIONS

- Extremely flammable.
- Avoid repeated skin contact or the breathing of concentrated vapours.
- Use in well ventilated areas away from heat, sparks, fire, flame and ignition sources.
- Vapours are heavier than air and may travel a considerable distance to an ignition source and flash back.
- Prior to working with any product, be sure to read labels and the Safety Data Sheet (SDS). Take necessary health and safety precautions.